

LIFTING INNOVATION

C22,000

The multi-directional forklift designed for the safe, space saving and productive handling of long and bulky loads.














REF.	DESCRIPTION	C22,000
1a	Max. Lift Height	1611/2"
1b	Free Lift Height	0"
2	Height Mast Closed	136″
3	Max. Mast Raised	2281/2"
4	Overall Length	121″
5	Mast travel	68¼"
6	Ground Clearance Under Mast	111/2"
7	Ground Clearance to Center of Wheelbase	6½"
8	Height Over Cab (without work lights)	102"
9	Width	110¼"
10	Outside Spread of Fork Arms	63"
11	Track Front	981/2"
12	Frame Opening	65"
13	Load Center Distance	24"
14	Overhang Front	12¼"
15	Wheelbase	100³/4″
16	Overhang Back	81/4"
17	Length from Face of Fork	541/2"
18	Approach Angle	45°
19	Ramp Angle	29°
20	Departure Angle	45°
21	Forward Tilt	3°
22	Backward Tilt	5°
23	Minimum Outside Radius	1221⁄4″
24	Platform Height	301/2"
25	Platform Length	661/2"
Α	Capacity	22,000 lbs
В	Unladen Weight	30,850 lbs
С	Maximum Ground Speed	8½ mph
D	Gradeability	15%
Е	Kubota V3800 -TE Diesel / 4.3 ltr GM LPG	99 HP / 96 HP
F	Electrics	12 Volt
G	Fork Section	2½" x 8" x 66½"
Н	22 x 12 - 16 Front Tire	OD 22" / Width 12"
- 1	840 / 340 - 559 Rear Tire	OD 33" / Width 133/4"
J	Standard Color	Green & Gray
K	Suspension Seat	KAB Model 211

European Patent No. 2167416; Brazilian Patent No. P10811954-6; Australian Patent No. 2008253242


Features Include:


Distributed by:

- Rubber Mounted Half Open Cabin
- Multi-Directional Operation
- 3 Wheel Hydrostatic Drive
- Load Sensing Steering
- 4 Way Lever Positioning of Wheels
- Hydraulic Oil Cooler









303 Concord Street, Greensboro, North Carolina 27406 Toll free: 1-877 COMBI 56 Tel: 336-378-8884 info@combilift.com

Combilifi has a policy of continuous product development and reserves the right to alter specifications without prior notice. Specifications and/or dimensions may vary from those illustrated in some countri-