

LIFTING INNOVATION

C6,000-C10,000

The multi-directional forklift designed for the safe, space saving and productive handling of long and bulky loads.









REF.	DESCRIPTION	C6,000	C8,000	C10,000
1a	Max. Lift Height	159"		
1b	Freelift Height	0"		
2	Height Mast Closed	113″		
3	Max. (Mast raised)	192"		
4	Overall Length	77"	91"	98"
5	Mast Travel	37"	51"	55"
6	Ground Clearance Under Mast	6"		
7	Ground Clearance to Center of Wheelbase	8"		
8	Height Over Cab (Without work lights)	96"		
9	Width	86"		
10	Outside Spread of Fork Arms	53"		
11	Track Front	78"		
12	Frame Opening	55"		
13	Load Center Distance	24"		
14	Overhang Front	10"		
15	Wheelbase	62"	75"	83"
16	Overhang Back	6"		
17	Length From Face of Fork	47"	47"	49"
18	Approach Angle	45°		
19	Ramp Angle	29°		
20	Departure Angle	45°		
21	Forward Tilt	3°		
22	Backward Tilt	5°		
23	Minimum Outside Radius	78"	92"	98"
24	Platform Height	21"		
25	Platform Length	33"	47"	53"
Α	Capacity	7,700 lbs	8,800 lbs	11,000 lbs
В	Unladen Weight	13,300 lbs	13,800 lbs	15,000 lbs
С	Maximum Ground Speed	9 mph		
D	Gradeability	15%		
Е	Kubota V2403 T Diesel / 3 ltr GM LPG	60 HP / 65 HP		
F	Electrics	12 Volt		
G	Fork Section 6" x 2" x	33"	47"	53"
Н	200 / 50 x 10 Front Tire	OD 18" / Width 8"		
I	27 x 10 - 12 Rear Tire	OD 27"/ Width 10"		
J	Standard Color	Green and Gray		
K	Suspension Seat	KAB Model 116		

European Patent No. 2167416; Brazilian Patent No. P10811954-6; Australian Patent No. 2008253242 Distributed by:

14

Features Include:

Rubber Mounted Cabin

- Multi-Directional Operation
- 3 Wheel Hydrostatic Drive
- **Load Sensing Steering**
- 4 Way Lever Positioning of Wheels
- Hydraulic Oil Cooler

303 Concord Street Greensboro North Carolina 27406 Toll Free: 1-877 COMBI 56

SIDEWARD MODE

FRONTAL MODE

Tel: 336-378-8884 info@combilift.com