

C6,000E-C10,000E


The electric multi-directional forklift designed for the safe, space saving and productive handling of long and bulky loads.





COMBi C-Series


combilift.com

| REF. | DESCRIPTION | C6000 E | C8000 E | C10,000 E |
|------|---|--------------------|------------------|------------------|
| 1a | Max. Lift Height | 159″ | | |
| 1b | Freelift Height | 0" | | |
| 2 | Height Mast Closed | 112″ | | |
| 3 | Max. (Mast raised) | 192″ | | |
| 4 | Overall Length | 77″ | 91″ | 98″ |
| 5 | Mast Travel | 37″ | 51″ | 57″ |
| 6 | Ground Clearance Under Mast | 6" | | |
| 7 | Ground Clearance to Center of Wheelbase | 41/4" | | |
| 8 | Height Over Cab (without work lights) | 96″ | | |
| 9 | Width | 89" | | |
| 10 | Outside Spread of Fork Arms | 53″ | | |
| 11 | Track Front | 79³⁄4″ | | |
| 12 | Frame Opening | 55″ | | |
| 13 | Load Center Distance | 18″ | 24″ | 24″ |
| 14 | Overhang Front | 83/4" | | |
| 15 | Wheelbase | 61" 75" 801/2" | | |
| 16 | Overhang Back | 5″ | | |
| 17 | Length From Face of Fork | 47″ | 47″ | 49″ |
| 18 | Approach Angle | 45° | | |
| 19 | Ramp Angle | 17° | | |
| 20 | Departure Angle | 45° | | |
| 21 | Forward Tilt | 3° | | |
| 22 | Backward Tilt | 5° | | |
| 23 | Minimum Outside Radius | 783⁄4″ | 911/2″ | 98″ |
| 24 | Platform Height | 19″ | | |
| 25 | Platform Length | 331/2" | 47″ | 53″ |
| А | Capacity | 6000 lbs | 8000 lbs | 10,000 lbs |
| В | Unladen Weight | 13,900 lbs | | 15,100 lbs |
| С | Maximum Ground Speed | 6 mph | | |
| D | Gradebility | 10% | | |
| Е | Battery Capacity | 80 V / 620 Ah | | |
| F | Fork Section | 2" x 6" x 33½" | 2" x 6" x 47" | 2″ x 6″ x 53″ |
| G | 405 x 305 x 220 Front Tire (Solid Rubber) | OD 16" / Width 9" | | |
| Н | 27 x 10-12 Rear Tire | OD 27" / Width 10" | | |
| | Standard Color | Green & Gray | | |
| J | AC Electric Traction Motor x 2 | 80 V / 7 HP | | |
| K | AC Electric Pump Motor | 80V / 25 HP | | |









303 Concord Street Greensboro North Carolina 27406 Toll free: 1-877 COMBI 56 Tel: 336-378-8884

C6,000E - C10,000E

Distributed by:

es the right to alter specifications without prior potice. Specifications and/or dimensions may vary from those illustrated in some countries

- Rubber Mounted Cabin •
- AC Motor Technology
- Multi-Directional Operation
- Load Sensing Steering
- Curtis AC Software
- 4 Way Lever Positioning of Wheels
- 2 Wheel Drive

Combilift has a policy of continuous product development and r

Features Include:

info@combilift.com

combilift.com