

10MSP

MOBILE STOCK PICKER

JLG
reachingout®

Performance

Platform Height	10 ft	3.05 m
Working Height	16 ft	4.88 m
Drive Height	Max. Platform Height	
Stowed Height	57 in.	145 cm
Platform Entry Height	13.75 in.	35 cm
Platform Size (W x L)	20 x 27 in.	49.5 x 69 cm
Overall Vehicle Length		
Chassis Length	61 in.	155 cm
Overall Vehicle Width		
Chassis Width	32.5 in.	83 cm
Chassis Width (without bumper)	29.5 in.	75 cm
Gross Vehicle Weight	1,100 lb	499 kg
Capacity		
Platform	350 lb	159 kg
Carry Deck	250 lb	113 kg
Material Tray	250 lb	113 kg
Max. Drive Speed		
Platform Lowered	5.0 mph	8.0 km/h
Platform Elevated	0.5 mph	0.8 km/h
Turning Radius	Zero	
Gradeability	15%	
Underclearance	2 in.	5 cm

Standard Specifications

Power Source

Batteries	4 Sealed 210 amp-hr Maintenance Free (AGM)	
Battery Charger	25 Amp Automatic	
Drive System	4 Brush Direct Electric (planetary gear)	

Tires

Rear Drive & Steer Wheels	12.62 x 4 in.	32 x 10 cm
Non-Marking Front Caster Wheels	8 x 2.5 in.	20 x 6 cm



Standard Features

- Heavy Duty Planetary Gear Drive Motors
- Simultaneous Lift and Drive Capability
- Point & Go® One-Hand Drive and Steer System
- Proportional Drive
- Automatic Five-Hour Battery Charger
- Battery Discharge Indicators — Platform and Base
- Lubrication-Free Anodized Aluminum Mast Sections
- Maintenance-Free Mast Guide System
- Strobe Lights Front and Rear
- Programmable Motion Alarm
- Slope Cut-Out Control Interlock
- Stand-On Foot Switch Operation Enable Control
- Platform Gate Operation Interlock
- Adjustable Height Material Tray
- Non-Marking Tire Material
- Lanyard Attachment Anchor Point
- Hourmeter
- Horn
- Shipping Skid
- Transportation Tie Downs
- Side and Front Bumpers
- ANSI, OSHA & CSA Compliant

Accessories & Options

- Charger Cord Retractor
- Programmable 4-Digit Security Lock
- Bike Carrier
- Rug Carrier
- Fluorescent Light Tube Caddy
- Guide Roller System
- Remote Manual Descent
- Object Sensing Pad
- Electrically-Powered Material Tray (200lb Capacity)
- Rubber Floor Mat

The JLG "1 & 5" Warranty

We provide coverage for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable ANSI and CSA requirements based on machine configuration as originally manufactured for intended applications. Please reference the serial number plate on the machine for additional information.

Form No.: SS-10MSP-0107-10M
Part No.: 3132119
R121707
Printed in USA

JLG
®

JLG Industries, Inc.

1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

An Oshkosh Corporation Company