

STAND-UP RIDER

KEY FEATURES

STRONG & WEAK POINTS

TOYOTA 8FBA15-25U



Battery Voltage (V)	36
Load Capacity (lbs)	3000 - 5000
Load Center (in)	24
Maximum Lift Height (in)	270.5
Travel Speed with/without Load (mph)	8.0/8.0
Lift Speed with/without Load (fpm)	100/130
Lower Speed with/without Load (fpm)	113/103
Turning Radius (in)	53.1 - 63
Overall Width (in)	41 - 46
Length to Fork Face (in)	66.5 - 77
Height of Overhead Guard (in)	88
Step Height (in)	9.4

- ✓+ 5000 lb Capacity
- ✓+ Suspension Floorboard
- ✓+ High Visibility Mast (4-Cylinder)
- ✓+ Multifunction Handle - Ease of Use, Precision Control
- ✓+ Adjustable Armrest and Tiller
- ✓+ Industry Leading Travel, Lift and Lower Speeds
- ✓+ Two Pillar Overhead Guard - High RH Side Visibility

ADDITIONAL NOTES

Optional Compartment Sensing System
500 Hour PM Interval
5000 lb Capacity Provides Best Capacity at Height
T360 Support Plus Option - Extended Warranty + 1 Year Free

CROWN RC SERIES



Battery Voltage (V)	36
Load Capacity (lbs)	3000 - 4000
Load Center (in)	24
Maximum Lift Height (in)	282
Travel Speed with/without Load (mph)	7.2/7.8
Lift Speed with/without Load (fpm)	65/110
Lower Speed with/without Load (fpm)	90/90
Turning Radius (in)	51.7 - 62.8
Overall Width (in)	42
Length to Fork Face (in)	64.3 - 75.8
Height of Overhead Guard (in)	88
Step Height (in)	9.5

- 5000 lb Capacity Not Available
- Slower Performance
- + 500 Hour PM Interval
- Noisy Gearbox / Mast Rattle /Mast Staging

ADDITIONAL NOTES

Component Access is Restricted
Optional Adjustable Armrest

HYSTER E30-40AD SERIES



Battery Voltage (V)	36
Load Capacity (lbs)	3000 - 4000
Load Center (in)	24
Maximum Lift Height (in)	288
Travel Speed with/without Load (mph)	8.0/8.0
Lift Speed with/without Load (fpm)	77/118
Lower Speed with/without Load (fpm)	102/98
Turning Radius (in)	51.3 - 57.4
Overall Width (in)	42.4
Length to Fork Face (in)	65 - 71.5
Height of Overhead Guard (in)	88
Step Height (in)	9.3

- 5000 lb Capacity Not Available
- + Suspension Floorboard with No Adjustment Required
- + Much Improved Performance Over Previous Model
- Common Items are Considered Options

ADDITIONAL NOTES

Optional Adjustable Armrest

LINDE E18S/E20S SERIES



Battery Voltage (V)	36
Load Capacity (lbs)	3500 - 4000
Load Center (in)	24
Maximum Lift Height (in)	276.5
Travel Speed with/without Load (mph)	7/7.5
Lift Speed with/without Load (fpm)	65/107
Lower Speed with/without Load (fpm)	95/85
Turning Radius (in)	55 - 57
Overall Width (in)	42.5
Length to Fork Face (in)	68 - 70
Height of Overhead Guard (in)	88
Step Height (in)	8

- 5000 lb Capacity Not Available
- + Adjustable Steer Tiller and Adjustable Armrest
- + Low Step Height
- + 1000 Hour PM Interval
- Slowest Overall Performance

ADDITIONAL NOTES

3 Year/6000 Hour Standard Warranty

JUNGHEINRICH ETG SERIES



Battery Voltage (V)	36
Load Capacity (lbs)	3000 - 4000
Load Center (in)	24
Maximum Lift Height (in)	276
Travel Speed with/without Load (mph)	8.0/8.0
Lift Speed with/without Load (fpm)	83/118
Lower Speed with/without Load (fpm)	102/98
Turning Radius (in)	50.8 - 57.8
Overall Width (in)	41
Length to Fork Face (in)	63 - 70
Height of Overhead Guard (in)	88
Step Height (in)	9.4

- 5000 lb Capacity Not Available
- Suspension Floorboard Requires Adjustment
- + Adjustable Armrest
- + 1000 Hour PM Interval
- + Smaller Tiller = More Space in Compartment

ADDITIONAL NOTES

2 shifts, 1 charge: Guaranteed