



# C15

IC- PNEUMATIC LPG  
 3000 / 3500 / 4000 lbs.  
 (1500 / 1800 / 2000 kg)

## STANDARD SPECIFICATIONS

## C15/18/20s

Manufacturer's Designation		C15	C18	C20s
Load Capacity / Rated Load	lbs(kg)	3000 (1500)	3500 (1800)	4000 (2000)
Height Overhead Guard	in(mm)	83.5 (2120)	83.5 (2120)	83.5 (2120)
Width	in(mm)	42.1 (1070)	42.1 (1070)	42.1 (1070)
Right Angle Stack (add load length & clearance)	in(mm)	STD 97.9 (2465) / TSU 97.1 (2468)	STD 98.9 (2513) / TSU 99.0 (2516)	STD 100.2 (2546) / TSU 100.3 (2549)
Outside Turning Radius	in(mm)	81.6 (2073)	83.5 (2121)	84.8 (2154)
Travel Speed Loaded / Unloaded	mph (kph)	10.8/11.4 (17.4/18.4)	10.7/11.4 (17.2/18.4)	10.6/11.0 (17.0/17.7)
Power Unit	HP(KW) @ rpm	PSI 2.0L 49.3 (36.8) @ 2650	PSI 2.0L 49.3 (36.8) @ 2650	PSI 2.0L 49.3 (36.8) @ 2650

## STANDARD FEATURES

- PSI Tier-4 2.0L Engine • EPA Compliant • Standard, Triple and Hi-Lo Uprights • Full Range of Lift Heights
- High Visibility “Silent Staging” Uprights • Single Speed Powershift Transmission • Cowl Mounted Levers
- Power Steering • Tilt Steering Wheel • Rear Handle with Horn Button • Static Vinyl Safety Seat • Orange Seatbelt • Traction Disable Seat Switch • Operator Presence System • Raised Air Intake • Open Core Radiator
- High Capacity Cooling System • Automatic Engine Shutdown System



For more information on this model and full line of CLARK Forklifts, find your local CLARK Dealer at [www.clarkmhc.com](http://www.clarkmhc.com)