



ECX

**ELECTRIC 36/48 VOLT
COUNTERBALANCED FOUR-WHEEL
4000 / 5000 / 6000 / 6500 lbs.
(2000 / 2500 / 3000 / 3000 kg)**

STANDARD SPECIFICATIONS

20/25/30/32

Manufacturer's Designation		ECX20	ECX25	ECX30	ECX32
Load Capacity / Rated Load @ 24" LC	lbs(kg)	4000 (2000)	5000 (2500)	6000 (3000)	6500 (3000)
Height Overhead Guard	in(mm)	88 (2235)	88 (2235)	88 (2235)	88 (2235)
Width	in(mm)	41.9 (1063)	43.9 (1114)	43.9 (1114)	45.4 (1154)
Right Angle Stack (add load length & clearance)	in(mm)	86.6 (2204)	89.7 (2279)	91.3 (2319)	96.2 (2444)
Outside Turning Radius	in(mm)	70.2 (1783)	72.6 (1845)	73.9 (1877)	78.3 (1989)
Travel Speed Loaded / Unloaded	mph (kph)	9.2/11.3 (14.8/18.2)	9.1/11.0 (14.6/17.7)	8.7/10.8 (14.0/17.4)	8.0/10.4 (12.9/16.7)
Power Unit		36 volt / 48 volt	36 volt / 48 volt	36 volt / 48 volt	36 volt / 48 volt

STANDARD FEATURES

• 100% AC Technology • Enclosed Motors • Advanced Thermal Protection For All Motors and Controls • Quiet, Non-Polluting Operation • Hydraulic Cushioning in Lift Mechanism • Adjustable Steering Pylon • Large Instrument Dash Display • Variety of Lights, Alarms and Other Options Are Available



For more information on this model and full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com