



SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

STANDARD FEATURES

- Electric drive
- ▶ LeakGuard®
- ▶ Drive at full height indoor & outdoor
- ▶ 110V power-to-platform
- Proportional controls
- > 30A charger
- Non-slip deck
- ▶ All motion alarm
- ▶ Flashing beacon
- ▶ Removable platform controls
- Self-locking gate
- Liftable with forklift or crane

- Dual maintenance bars
- Onboard diagnostic system
- Manual decent cable
- Active tilt alarm
- ▶ Slide out extension
- Automatic pothole protection
- Non-marking tires
- Horn
- ► CAN communication protocol
- > 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

NSI A92.20

EL-3245e

OPTIONS

- Perimeter Lights
- ▶ Pipe Rack

EL-3245e SCISSOR

Hydraulic Tank Capacity

Battery

SPE	CIFICATIONS		
A	Working Height (2 Person Indoor/1 Person Outdoor)	38.8 ft	12 m
В	Platform Height Maximum (2 Person Indoor/1 Person Outdoor)	32.8 ft	10 m
С	Platform Height Minimum	52.8 in	1.34 m
D	Ground Clearance Elevated	0.79 in	2 cm
E	Ground Clearance Lowered	4.7 in	12 cm
F	Overall Length w/Step	97.3 in	2.47 m
G	Overall Width	45 in	1.15 m
Н	Stowed Height (Rails Unfolded)	96.1 in	2.44 m
	Stowed Height (Rails Folded)	73.2 in	1.86 m
1	Platform Length	91 in	2.31 m
J	Platform Width	45 in	1.14 m
К	Slide Out Extension Deck Length	39.4 in	1 m
	Wheelbase	73.2 in	1.86 m
	Tires	15 x 5 in	38 x 12.7 cm

Rated Occupancy (Indoor/Outdoor)	2 / 1 Person(s)		
Rated Occupancy (Indoor/Outdoor)	2/110	213011(3)	
Platform Capacity	661 lbs	300 kg	
Slide Out Extension Deck Capacity	330 lbs	150 kg	
Gradeability	2!	25%	
Inside Turn Radius	0 in	0 cm	
Drive Speed Elevated	0.4 mph	0.6 km/h	
Drive Speed Lowered	2.8 mph	4.5 km/h	
Working Slope	2°/3°		
Lift Speed (Up/Down)	60 / 47 sec		
Weight	6,393 lbs	2,900 kg	

7.1 gal

27L

4 x 6V 315 Ah

