



## EL-4555XCe SCISSOR



## EL SERIES

### SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

#### STANDARD FEATURES

- ▶ Electric drive
- ▶ LeakGuard®
- ▶ Indoor & outdoor operation settings
- ▶ 110V power-to-platform
- ▶ Proportional controls
- ▶ 30A charger
- ▶ Non-slip deck
- ▶ All motion alarm
- ▶ Flashing beacon
- ▶ Removable platform controls
- ▶ Self-locking gate
- ▶ Liftable with forklift or crane
- ▶ Dual maintenance bars
- ▶ Onboard diagnostic system
- ▶ Manual decent cable
- ▶ Active tilt alarm
- ▶ Slide out extension
- ▶ Automatic pothole protection
- ▶ Non-marking tires
- ▶ Horn
- ▶ CAN communication protocol
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

#### STANDARDS COMPLIANCE

- ▶ ANSI A92.20

#### OPTIONS

- ▶ Perimeter Lights
- ▶ Pipe Rack

# EL-4555XCe

## SCISSOR

SPECIFICATIONS			
A	Working Height (2 Person Indoor)	51.6 ft	15.75 m
	Outdoor Working Height (1 Person Outdoor)	38 ft	11.6 m
B	Platform Height Maximum (2 Person Indoor)	45.1 ft	13.75 m
	Outdoor Platform Height Maximum (1 Person Outdoor)	32 ft	9.75 m
C	Platform Height Minimum	63 in	1.6 m
D	Ground Clearance Elevated	0.79 in	2 cm
E	Ground Clearance Lowered	4.7 in	12 cm
F	Overall Length w/Step	109.8 in	2.79 m
G	Overall Width	55 in	1.39 m
H	Stowed Height (Rails Unfolded)	103.9 in	2.64 m
	Stowed Height (Rails Folded)	83.5 in	2.12 m
I	Platform Length	105.5 in	2.68 m
J	Platform Width	45.3 in	1.15 m
K	Slide Out Extension Deck Length	39.4 in	1 m
Wheelbase		87.4 in	2.22 m
Tires		15 x 5 in	38 x 12.7 cm

PERFORMANCE			
Rated Occupancy (Indoor/Outdoor)		2 / 1 Person(s)	
Platform Capacity		771.6 lbs	350 kg
Slide Out Extension Deck Capacity		330.7 lbs	150 kg
Gradeability		25%	
Drive Speed Elevated (Proportional)		0.37 mph	0.6 kph
Drive Speed Lowered (Proportional)		2.8 mph	4.5 kph
Working Slope		2° / 3°	
Lift Speed (Up/Down)		77 / 62 sec	

POWER			
Hydraulic Tank Capacity		7.4 gal	28 L
Battery		4 x 12V 300 Ah	

