



HY-BRID LIFTS 
MADE IN THE USA

ZT-1230 SCISSOR



ZERO-TURN SERIES

SELF-PROPELLED MOBILE ELEVATED WORK PLATFORM

STANDARD FEATURES

- ▶ Proportional controls
- ▶ Electric drive & steer
- ▶ 110V-AC power to platform
- ▶ LeakGuard™ ready
- ▶ Indoor/outdoor operation settings
- ▶ Horn
- ▶ Maintenance charger
- ▶ Intelligent control system
- ▶ Total control drive system
- ▶ Manual descent pull cable
- ▶ Dual maintenance locks
- ▶ Active tilt alarm
- ▶ Active load-sensing
- ▶ Low floor load pressures
- ▶ Pothole protection
- ▶ Forklift pockets
- ▶ Zero-turn radius
- ▶ EZ-Glide slide out extension
- ▶ 25% gradeability
- ▶ Solid rubber, non-marking wheels
- ▶ Default upper control setting
- ▶ Locking front wheel casters
- ▶ Removable platform controls
- ▶ 2-year parts & labor warranty
- ▶ 5-year structural warranty

STANDARDS COMPLIANCE

- ▶ ANSI A92.20
- ▶ CSA B354.6:17

OPTIONS

- ▶ LeakGuard™
- ▶ AGM Battery
- ▶ Flashing beacon
- ▶ All motion alarm
- ▶ Inverter

ZT-1230

SCISSOR

SPECIFICATIONS			
A	Working Height (1 Person Indoor)	18 ft	5.5 m
	Working Height (2 Person Indoor/1 Person Outdoor)	13 ft	3.96 m
B	Platform Height Maximum (1 Person Indoor)	12 ft	3.7 m
	Platform Height Maximum (2 Person Indoor/1 Person Outdoor)	7 ft	2.1 m
C	Platform Height Minimum	21 in	53.3 cm
D	Ground Clearance Elevated	0.5 in	1.3 cm
E	Ground Clearance Lowered	3.6 in	9.1 cm
F	Overall Length w/ Step	62 in	157.5 cm
G	Width	30 in	76.2 cm
H	Stowed Height	65 in	165.1 cm
I	Platform Length	53 in	134.6 cm
J	Platform Width	24 in	61 cm
K	Slide Out Extension Deck Length	30 in	76.2 cm
Wheelbase		46.5 in	118.1 cm
Tires (Front/Rear)		8/12 in	20.3 x 30.5 cm

PERFORMANCE			
Rated Occupancy (Indoor/Outdoor)		2/1 Person(s)	
Platform Capacity		650 lbs	294.8 kg
Slide Out Extension Deck Capacity		250 lbs	113.4 kg
Gradeability		25%	
Inside Turn Radius		Zero	
Drive Speed Elevated		0.9 mph	0.4 km/h
Drive Speed Lowered		2.7 mph	1.2 km/h
Lift Speed (Up/Down)		18 / 18 s	
Weight		1,616 lbs	733 kg
Wheel Load at Minimum Capacity		134.9 psi	930.1 kPa
Wheel Load at 500 lbs Capacity		166.6 psi	1,148.7 kPa
Wheel Load at Maximum Capacity		177.5 psi	1,223.8 kPa

POWER			
Hydraulic Tank Capacity		1 gal	3.55 L
Battery		2 x 12V Group 27	

